

Concordia Industrial & Trading Ltd.

H-1118, Budapest, Naprózsa utca 6. Phone: (+36) 1 309-0530, Fax: (+36) 1 309 0539

E-mail: info@concordia-zipper.hu Web: www.concordia-zipper.hu



TECHNICAL DATA SHEET


Two Way Close-End Polyester coil Zip-fastener

RTO - ZTX



Raw Materials	
Chain	polyester monofilament
Таре	polyester yarn
Top Stops	aluminum
Slider	zinc alloy

Dimensions (1)				
Chain width	b	4,10 - 4,25 mm		
Width of fastener	В	24,00 - 26,00 mm		
Tape width t		12,00 - 13,00 mm		
Monofilament diameter	0	0,50 mm		





Concordia Industrial & Trading Ltd.

H-1118, Budapest, Naprózsa utca 6. Phone: (+36) 1 309-0530, Fax: (+36) 1 309 0539

E-mail: info@concordia-zipper.hu Web: www.concordia-zipper.hu



Functional properties (1)			
Slider moving force	< 6 N		
Slider locking force	> 70 N		

Mechanical properties (1)				
Lateral strength of fastener	> 350 N			
Strength of top stops	> 60 N			
Strength of puller attachment	> 70 N			

Resistance to reciprocation (1)

Tearing strength of zippers tired with 300 tiring section (open-close) was not less then 90% of the standards without tiring.

Color fastness (2)					
Color fastness to light	7	MSZ 2102-2			
Color fastness to washing 60 °C	5/5/5	MSZ EN 20105 CO 3			
Color fastness to dry cleaning	5/5	MSZ 2104-1			
Color fastness to perspiration (alkaline, acid)	5/5/5	MSZ 2105-4			
Color fastness to dry/wet rubbing.	5/4-5	MSZ 2111-1			

- (1) According to the following standards: MSZ 8813/1, MSZ 8813/2, DIN 3417, DIN 3418, and DIN 3419-1. The tests were made by Concordia's own laboratory. The verification tests were made by ÉMI-TÜV SÜD Ltd.'s (KERMI) laboratory.
- (2) Color fastness tests were made by ÉMI-TÜV SÜD Ltd.'s (KERMI) laboratory.

[•] Available sliders:





Concordia Industrial & Trading Ltd.

H-1118, Budapest, Naprózsa utca 6. Phone: (+36) 1 309-0530, Fax: (+36) 1 309 0539

E-mail: info@concordia-zipper.hu Web: www.concordia-zipper.hu









ROPA

R0GA-0

R0M2A

Non Lock Sliders





R₀CL

R0BCL*

- [•] **Human ecology information:** all of raw materials that were used under productions of this type of zip fastener and all of dyestuffs and textile chemicals were used to dyeing and finishing of this type of zip fastener are corresponding to the Oeko-Tex Standard 100 product class II. The nickel plated sliders are may unsafe in case of direct skin contact aspect of human ecology because of their nickel content.
- [•] **Suggested applications:** outerwear from thin woven or knitted clothes. Trousers from thin fabrics.
- [•] Handling requirements:











^{*}fancy slider, made of Delrin, without puller, especially for bed cloth zippers